

DIGI® Bench Scale and Indicator Package



Approvals



Measurement
Canada
Approved

Standard Features

- Large 0.8" (20.3 mm) six-digit red light emitting diode (LED) display
- 115 or 230 VAC
- EPD and printer port for connecting to a PC or printer
- Programmable print output strings
- Available in 150 lb/60 kg, 300 lb/150 kg, 500 lb/300 kg capacities
- Selectable unit of measure lb/kg/g/oz
- Load cell quick disconnect
- Carbon steel platform, stainless steel platter (STL)
- 120 wall mount bracket included

Specifications

LINE VOLTAGES:

115 or 230 VAC

FREQUENCY:

50 or 60 Hz

EDP PORT:

Full duplex RS-232

PRINTER PORT:

Output-only RS-232 or active 20 mA current loop

BOTH PORTS:

9600, 4800, 2400, 1200, 600, 300 bps; seven or eight data bits; even, odd or no parity

PRINT OUTPUT STRINGS:

300 character user programmable gross string
300 character user programmable net string

DISPLAY:

0.8" (20.3 mm), 6-digit Super Red Light Emitting Diode (LED) display, seven-segment, number digits

ANNUNCIATORS:

Eight LEDs, 4 unit descriptors

ADDITIONAL SYMBOLS:

Designators for: center of zero, stand still, gross, net center of zero, standstill, lb, kg, oz, g

KEYBOARD:

Five-key flat membrane panel

OPERATING TEMPERATURE:

-10°C to 40°C/14°F to 104°F (legal)
-10°C to 50°C/14°F to 122°F (industrial)

RATING/MATERIAL:

Enclosure: heavy gauge ABS

SCALE APPROVALS:


NTEP-certified per H-44, Class III, 5000d, Measurement Canada approved, AM-5393

INDICATOR APPROVALS:

NTEP-certified per H-44 at 10,000 Divisions, Class III/IIIL, CC# 03-059; Measurement Canada approved, Class III/IIHHD at 10,000 Divisions; TC6008; UL & CUL listed; CE marked

WARRANTY:

One-year limited warranty



DIGI BENCH SCALE AND INDICATOR PACKAGE

PART #	CAPACITY	EST. SHIP WEIGHT	A	B	C	D	E	F
83303	150 lb/60 kg x 0.05 lb/0.02 kg	57 lb	20.44"	24.6"	16.31"	3.94"	23.9"	32.6"
			(519.17 mm)	(624.84 mm)	(414.27 mm)	(100.07 mm)	(607.06 mm)	(828.04 mm)
83304	300 lb/150 kg x 0.1 lb/0.05 kg	57 lb	20.44"	24.6"	16.31"	3.94"	23.9"	32.6"
			(519.17 mm)	(624.84 mm)	(414.27 mm)	(100.07 mm)	(607.06 mm)	(828.04 mm)
83305*	500 lb/300 kg x 0.1 lb/0.1 kg	57 lb	20.44"	24.6"	16.31"	3.94"	23.9"	32.6"
			(519.17 mm)	(624.84 mm)	(414.27 mm)	(100.07 mm)	(607.06 mm)	(828.04 mm)

* Measurement Canada Approved