

Intercomp CS™ 200



Standard Features

- Lightweight and compact
- Digital calibration
- Auto shut-off
- lb/kg selectable
- Peak hold feature

Specifications

RESOLUTION:

12 bit A/D delivers more than 1 million internal counts

CONTROLS:

Zero, lb/kg, on/off

DISPLAY:

0.5" (12 mm) 5-digit LCD

POWER:

One 9V disposable alkaline dry cell (or rechargeable nickel-cadmium cell, not included) Battery life is one year of normal use.

DIMENSIONS:

3.75" W x 2" D x 6" H
(94 mm W x 50 mm D x 150 mm H)

ENCLOSURE:

Weatherproof ABS plastic case

APPROVALS:

CE

AUTO SHUT-OFF:

Low battery, or after 5 minutes without use

ACCURACY:

±0.1% of applied load

TEMPERATURE:

Operating -4°F to 140°F
(-20°C to 60°C)

NOMINAL OVERLOAD:


200% of capacity

MAXIMUM OVERLOAD:

500% of capacity

WARRANTY:

One-year limited warranty



PART #	CAPACITY	GRADUATION	EST. SHIP WEIGHT
CS200			
43734	25 lb (12.5 kg)	0.01 lb (0.01 kg)	2 lb
43735	50 lb (25 kg)	0.02 lb (0.01 kg)	2 lb
43736	100 lb (50 kg)	0.05 lb (0.02 kg)	2 lb
43737	250 lb (125 kg)	0.1 lb (0.05 kg)	2 lb
82444	500 lb (250 kg)	0.2 lb (0.1 kg)	2 lb

Specifications subject to change without notice