

Intercomp TL 6000




Approvals



Standard Features

- Aluminum, stainless steel, or alloy steel construction
- Peak hold feature
- Self contained display
- Optional wireless or hardwire readouts



Specifications

CONSTRUCTION:

Aluminum construction for 10,000 lb and below capacities
 Stainless steel construction for 25,000 lb to 160,000 lb capacities
 Aircraft alloy steel from 220,000 lb and above capacities

ACCURACY:

+/- 0.1% of applied load or +/-1 graduation; whichever is greater
 +/- 0.2% or +/-2 graduations for 25,000 and higher

DISPLAY:

Five digit, 1.2 inch (30 mm) high LCD

CONTROL KEYS:

On/Off, Zero (100%), Tare (100%), Peak Hold and Mode

ANNUNCIATOR:

Low Battery, Peak Hold, Set Points 1 & 2, lb, kg, tons, metric tons and dekaNewtons

POWER:

Two (9V) batteries (batteries included)

OPERATING TIME:

Up to 300 hours of continuous use. Wireless remote control models have reduced operating time of 50 hours.

OPERATING TEMPERATURE:

-4° F to 140° F (-20° C to 60° C)

ENCLOSURE:

NEMA 4X/IP 65

OVERLOAD:

200% safe, 500% ultimate

CALIBRATION:

Digital keypad, multi-point

OUTPUT:

RS-232 and RS-485

PN	CAPACITY	RESOLUTION	A	B	C	D	E	F	G	SHACKLE TYPE/CAPACITY
82490	500 lb (250 kg)	0.5 lb (0.2 kg)	13 in (304 mm)	0.81 in (21 mm)	7.42 in (178 mm)	1 in (25 mm)	1.69 in (43 mm)	2 in (51 mm)	4.75 in (121 mm)	G-2130-3 1/4 T
82491	1000 lb (500 kg)	1 lb (0.5 kg)	13 in (304 mm)	0.81 in (21 mm)	7.42 in (178 mm)	1 in (25 mm)	1.69 in (43 mm)	2 in (51 mm)	4.75 in (121 mm)	G-2130-3 1/4 T
82492	2,000 lb (1,000 kg)	2.0 lb (1 kg)	13 in (304 mm)	0.81 in (21 mm)	7.42 in (178 mm)	1 in (25 mm)	1.69 in (43 mm)	2 in (51 mm)	4.75 in (121 mm)	G-2130-3 1/4 T
82493	5,000 lb (2,500 kg)	5 lb (2 kg)	13 in (304 mm)	0.81 in (21 mm)	7.42 in (178 mm)	1 in (25 mm)	1.69 in (43 mm)	2 in (51 mm)	4.75 in (121 mm)	G-2130-3 1/4 T
82494	10,000 lb (5,000 kg)	10 lb (5 kg)	15.22 in (386 mm)	1.06 in (27 mm)	7.6 in (193 mm)	1.4 in (36 mm)	2.28 in (58 mm)	2.77 in (56 mm)	5 in (127 mm)	G-2130-6 1/2 T
82495	25,000 lb (12,500 kg)	20 lb (10 kg)	20.9 in (530 mm)	1.69 in (43 mm)	8.7 in (212 mm)	2.13 in (54 mm)	3.63 in (92 mm)	4.3 in (109 mm)	5 in (127 mm)	G-2130-13 1/2 T
82496	50,000 lb (25,000 kg)	50 lb (20 kg)	24.7 in (627 mm)	2.06 in (52 mm)	9.2 in (234 mm)	2.44 in (62 mm)	5 in (127 mm)	5.93 in (151 mm)	5 in (127 mm)	G-2130-25 T
82497	100,000 lb (50,000 kg)	100 lb (50 kg)	29.49 in (749 mm)	2.81 in (72 mm)	10.69 in (271 mm)	3.88 in (99 mm)	7.25 in (184 mm)	9.4 in (240 mm)	5 in (127 mm)	G-2130-55 T
82498	160,000 lb (80,000 kg)	200 lb (100 kg)	32.6 in (828 mm)	2.81 in (72 mm)	10.69 in (271 mm)	3.88 in (99 mm)	7.88 in (200 mm)	7.8 in (198 mm)	5.4 in (138 mm)	G-2140-85 T
82499	220,000 lb (110,000 kg)	200 lb (100 kg)	38.4 in (975 mm)	3.5 in (89 mm)	12.4 in (315 mm)	4.45 in (113 mm)	7.88 in (200 mm)	8.5 in (215 mm)	5.9 in (150 mm)	G-2140-120T
82500	350,000 lb (175,000 kg)	500 lb (200 kg)	44 in (1118 mm)	4.5 in (114 mm)	15 in (381 mm)	5.25 in (133 mm)	10 in (254 mm)	8.88 in (225 mm)	7 in (178 mm)	G-2140-175 T
82501	400,000 lb (200,000 kg)	500 lb (200 kg)	47.8 in (1118 mm)	5 in (127 mm)	16.57 in (421 mm)	7 in (178 mm)	11 in (279 mm)	9.37 in (237 mm)	7 in (197 mm)	G-2140-200 T
82502	500,000 lb (250,000 kg)	500 lb (200 kg)	62.55 in (1588 mm)	5.25 in (133 mm)	18.07 in (459 mm)	8.75 in (222 mm)	13 in (330 mm)	17.88 in (454 mm)	8.45 in (215 mm)	G-2140-250 T

* Dimensions are top to bottom shackle eye to eye on 25-50 ton/12.5-25 metric ton capacity models

*Unit comes standard with top shackle & bottom swivel hook. Capacities to 300 tons available upon request.

Specifications subject to change without notice